

## NEW AS2000HAT PROTECTIVE FACE SHIELD 20 CAL/CM<sup>2</sup> WEIGHT BALANCING ARC FLASH PROTECTION FACE SHIELD

**NEW REVOLUTIONARY AS2000HAT** - Salisbury by Honeywell's NEW revolutionary AS2000HAT is a Weight Balancing Arc Flash Protection Face Shield. The shield stows in a balanced, compact position, centered over the top of the hard hat when not in use. The AS2000HAT has an ATPV rating of 20 cal/cm<sup>2</sup> and utilizes nanotechnology to provide a clearer, more transparent window for improved visibility. The face shield unit includes ventilation ribs that allow a natural convection air flow through the top of the face shield. This reduces fogging of the visor, lowers CO<sub>2</sub> levels and improves comfort.

### NEW AS2000HAT SERIES

- 7.5" x 20" Viewing area
- Extra light tint
- .06" Thick
- Absorbs >99.9% of harmful UV radiation
- Resistant to fogging
- Meets current ANSI Z87.1 and is CSA standard compliant
- Tested to ASTM F2178 specifications



AS2000HAT



**NOTE:** IN ORDER TO ACHIEVE 360 DEGREE 20 CAL/CM<sup>2</sup> PROTECTION, A 20 CAL/CM<sup>2</sup> BALACLAVA MUST BE WORN.  
**NFPA70E:** AN ARC RATED HOOD SHALL BE USED WHEN THE ANTICIPATED INCIDENT ENERGY EXPOSURE EXCEEDS 12 CAL/CM<sup>2</sup>.

**AS1200HAT** - Salisbury by Honeywell's revolutionary AS1200HAT is a Weight Balancing Arc Flash Protection Face Shield, that stows in a balanced, compact position, centered over the top of the hard hat when not needed. The AS1200HAT has an ATPV rating of 12 cal/cm<sup>2</sup> and utilizes nanotechnology to provide a more transparent window for improved visibility. The shield/window is designed to be easily replaced without tools. The face shield unit includes ventilation ribs that allow a natural convection air flow through the top of the face shield. This reduces fogging of the visor, lowers CO<sub>2</sub> levels and improves comfort for the user.

### AS1200 SERIES

- 7.5" x 20" Viewing area
- Extra light tint
- .06" Thick
- Absorbs >99.9% of harmful UV radiation
- Resistant to fogging
- Meets current ANSI Z87.1 and is CSA standard compliant
- Tested to ASTM F2178 specifications



AS1200HAT

CAT. NO.	DESCRIPTION
AS2000HAT	<b>NEW</b> 20 cal/cm <sup>2</sup> , arc flash protection face shield unit w/SA79R03 hard hat
AS2000	<b>NEW</b> 20 cal/cm <sup>2</sup> , arc flash protection face shield unit
AS2000FS	<b>NEW</b> Replacement face shield/window
AS1200HAT	Weight balancing arc flash protection face shield unit w/hard hat
AS1200HAT-CLR	AS1200HAT w/ transparent chin guard
AS1200	Weight balancing arc flash protection face shield unit.